

STH-D1R- SMOKE DETECTORS

The unit can be fitted with smoke detectors, placed in supply and/or extract air duct. If the detector indicates smoke an alarm is triggered in Climatix.

STH-D1R-00	Control unit for smoke detectors. ABAV-S3
	Up to thirty smoke detectors, either ionizing or optical, can be serially connected. Upon alarm from any of the detectors, in this case Fire alarm 1 is triggered in Climatix.
	A 2.2 k Ω termination resistor is connected to the last detector in the series to ensure proper monitoring of the circuit.
STH-D1R-10	Smoke detector in supply air. Smoke detection triggers an alarm in control unit. (STH-D1R-00) <u>UG8-O</u>
STH-D1R-11	Smoke detector with built-in control unit in supply air. <u>UG8-E-24</u>
	Smoke detection triggers Fire alarm 1 in Climatix.
STH-D1R-12	Smoke detector with built-in control unit in supply air (DiBt approved) <u>UG-5-AFR-230V-Z</u>
	Smoke detection triggers Fire alarm 1 in Climatix.
STH-D1R-20	Smoke detector in extract air. Smoke detection triggers an alarm in control unit (STH-D1R-00) <u>UG8-O</u>
STH-D1R-21	Smoke detector with built-in control unit in extract air. <u>UG8-E-24</u>
	Smoke detection triggers Fire alarm 1 in Climatix.
STH-D1R-22	Smoke detector with built-in control unit in extract air (DiBt approved) <u>UG-5-AFR-230V-Z</u>
	Smoke detection triggers Fire alarm 1 in Climatix.